

SQLskills Immersion Training

IE1: Internals and Performance

Kimberly's Whiteboard Drawings and Annotations


Kimberly L. Tripp
Kimberly@SQLskills.com



NOTE: Includes whiteboard drawings from prior IE courses
+ drawings done the week of March 10, 2014
Sydney, NSW, Australia – IE1 Training

Performance Dashboard Reports on 2008/R2

A Quick Side Note/FYI



- SQL Server 2005 Performance Dashboard Reports (download from Microsoft Download Center)
- Install for 2005, copy the PerformanceDashboard directory to 100\Tools
 - 2005 path: C:\Program Files (x86)\Microsoft SQL Server\90\Tools\PerformanceDashboard
- Change the setup.sql
 - cpu_ticks_in_ms -> ms_ticks
 - 64bit datediff problem: <http://theskythelimit.blogspot.com/2008/03/fix-difference-of-two-datetime-columns.html> (<http://bit.ly/RqZerE>)
- Use the modified script in your script directories

Performance Dashboard Reports on 2012


A Quick Side Note/FYI



- SQL Server 2012 Performance Dashboard Reports have been updated (download from Microsoft Download Center)
 - <http://www.microsoft.com/en-us/download/details.aspx?id=29063>

Performance Dashboard Reports


A GENERAL Side Note/FYI



- **The Good (quick/easy)**
 - Looks at current, in-memory state
 - Good for overall server, generally bad queries, digging in and seeing some info but a lot of good info is hard to get
 - Easy to get at and easy to use if you want to get some insight into what's happening ***at a particular moment***
- **The Bad**
 - No historical information (PDC/PA – info on next slide)
 - Only good for “right now”
 - Doesn't give you access to the graphical plan directly: must export (only options are: Excel or pdf – *are you kidding??*) OR manually type in the sql/plan_handle and that's ***iff*** it's still in cache

Performance Data Collection

Resources/Why it's Not Covered in Class



- **For Performance Data Collection**
 - Microsoft eLearning Resources - Clinic 10259 (SQL 2008 DBIS)
 - [http://www.sqlskills.com/BLOGS/KIMBERLY/post/Microsoft-eLearning-Resources-Clinic-10259-\(SQL-2008-DBIS\).aspx](http://www.sqlskills.com/BLOGS/KIMBERLY/post/Microsoft-eLearning-Resources-Clinic-10259-(SQL-2008-DBIS).aspx) (<http://bit.ly/amRwEm>)
 - Performance Data Collection LAB
- **NOTE: There are many inefficiencies in PDC and no enhancements in the latest version (2012); that's why it's not a topic covered directly in class. Check out this great article for a comparison to SQL Sentry's Performance Advisor (similar but MUCH more extensive and efficient):**
 - Monitoring Your Servers : Data Collection vs. Performance Advisor, Aaron Bertrand
 - <http://www.sqlservercentral.com/articles/Product+Reviews/66278/>
 - Remember, you can download PE for free and you can also get a PA evaluation license for a 45 day trial as an Immersion Event attendee!

SQLskills Immersion Event

IE1: Internals and Performance


General Internals

Kimberly L. Tripp

Kimberly@SQLskills.com



NOTE: During Module 1 (Index Internals), we discussed *general database internals*; this first section is from these drawings.



One of the problems in allowing files to be added to the primary filegroup is that it makes it more vulnerable to downtime. SQL Server's Partial Database Availability feature **ONLY** works when both the primary filegroup **AND** the log are available. If the primary filegroup has multiple files and one of those files fails – the entire database will be offline until restored.


For VLDBs, you want to isolate the primary filegroup and dedicate it only to system tables. Then, place it on redundant disks.

Secondary, non-primary filegroups are where you'll store data.

(see the next drawing)

If VLDB

mdf just SYS RID x 3



PDA
if file damaged
only that file
offline

By dedicating only the system objects to the primary filegroup (and limiting this to only one, relatively-small mdf, you reduce the potential for downtime.

If a file does become damaged then the database can remain online and available (PDA). And, then, using Online Piecemeal Restores, you can keep your database online for most of the recovery process.

NOTE: Remember in my USB demo... there is one caveat. To take a file offline (in order to begin the restore process), you must take the filegroup of which it's a member offline. This is NOT an online operation (because SQL Server does not track transactions at the filegroup level). So, all connections to the database are terminated when you take a filegroup offline.



allocations?

After eight 8KB pages have been allocated to a table, SQL Server does extent-based allocations. These allocations are done file by file. Or, in other words, SQL Server round-robins extent allocations from the files in the filegroup.

This helps to reduce IO contention and also contention on the system allocation pages (GAM pages are used for extent allocations) themselves.


To the left – the first 4 pages in a file are:
 Header (0)
 PFS: Page Free Space (1)
 GAM: Global Allocation Map (2)
 SGAM: Shared Global Allocation Map (3)

IAM Pages

While GAM pages track extent usage within the database, IAM pages track a table's allocated extents within a GAM interval (a 4GB chunk of the file). GAM page and IAM pages can track 4GB because they use a bitmap structure on the 8KB page.

8KB = 8192 bytes = 65536 bits

With roughly 64000 bits each tracking an extent (64KB), you can see how they can track a 4GB chunk of the file.




From the Heap DEMO

In my heap demo, I first added rows (as fast as possible) in the table. All of the rows were fixed width and column 7 had only 11 bytes per row. SQL Server filled the pages as fast as they could...

Then, I went and updated col7 [varchar(200)] to be larger. This created forwarded rows. The original location for insert holds a forwarding pointer and that points to the new/final location of the record.

For more info: here's a detailed post that Paul did on this: <http://www.sqlskills.com/blogs/paul/forwarding-and-forwarded-records-and-the-back-pointer-size/>





Inserts on a page (1 of 2)

SQL Server does not rearrange the records on a page – unless it needs to.

If there are two records on a page but there's a gap large enough to fit the record being inserted, then SQL Server will put the record wherever it fits.

On a heap, it will receive the next slot available. On an indexed page, the slots will be ordered by the index key.




Inserts on a page (2 of 2)

SQL Server does not rearrange the records on a page – unless it needs to.

The same holds for an update. If the first record is being updated and there's not enough room without rearranging the page then SQL Server will rearrange.

If the record moves then the slot doesn't change but the offset will get updated.



Record Structures (1 of 2)

In_row fixed-width
All structures if ≤ 8060
note! never span pages
always be cont

Overflow limited VC Cds
Short LOBs
if row size > 8060 then
1+ cds w/overflow


Every table/index can have up to 3 data structures associated with it:

* In_row – every row has an in_row_data structure. This cannot exceed 8060 bytes and must exist as a single, contiguous structure on – at most – one page. If a row has limited variable columns [varchar(n), nvarchar(n) or varbinary(n)] or LOB types [new LOB types: varchar(max), nvarchar(max) or varbinary(max); Legacy LOB types: text, ntext, image; XML] then you *might* have additional structures.

* Overflow – Overflow is only for limited variable columns (often called SLOBs for short LOBs). A row will ONLY overflow to the overflow structure IF the row is over 8060 bytes AND only these limited LOBs will overflow to the overflow structure. Fixed-width columns will NOT overflow. An overflowed column will always overflow as a unit and the column(s) that overflows is not easily predictable.

* LOB – explained on next page.

Record Structures (2 of 2)



* LOB – There are 8 LOB types in SQL Server:

- New LOB types
 - varchar(max)
 - nvarchar(max)
 - varbinary(max)
 - XML
 - User-defined SQLCLR types
- Legacy LOB types
 - text
 - ntext
 - Image

The initial location of the LOB (on insert) will depend on the LOB data type you've used. The default behavior to legacy LOB was to push them off row – regardless of size. For the new LOB types they will put them in_row only if they fit.

You can control these options by using `sp_tableoption` for every table change.

For legacy LOB you can control the maximum byte length for in_row LOBs. For new LOB types they either go in_row if they fit (default) OR you can say they go off-page no matter what.

The cost of creating a clustered index

To create a clustered index, SQL Server needs to copy the data (in the filegroup that is the destination) as well as use sort space to order the data (also in the destination). For a 10GB table this requires 10GB for the copy and ~25% for the sort space. Then, there's logging – in a fully logged database (the default), this is essentially a "size of data" operation. So, for a 10GB table, this is a 10GB operation in the log. The total size for a create or rebuild in a fully logged database is 3.25x the table size.




Clustering for ranges (looks good on paper)

If I show you a clustered structure and talk ONLY about querying for ranges, I can convince you that you should create a clustered index on something like Lastname, Firstname, Middleinitial

And, while this looks good on paper, it doesn't last very long. As soon as inserts/updates occur, this table will become very fragmented. This fragmentation will offset (and begin to overshadow) the apparent benefits of having chosen that order.

And, I haven't even mentioned the expense of a wide clustering key in the nonclustered indexes.



SQLskills Immersion Event

IE1: Internals and Performance

Module 3: Locking and Blocking

Kimberly L. Tripp
Kimberly@SQLskills.com



Implicit / auto commit trans.

Set implicit_transactions on

Update

Insert

Commit tran

Explicit
Begin Tran


Commit Tran

S3

While discussing locking basics, we talked about ACID properties.

We also started to discuss transactions:


- *Implicit* is now auto-commit. In most people's minds implicit used to mean that SQL Server implicitly treats your statements as a transaction. However, Oracle's implicit begin a transaction for you and so these should not be confused. To reduce confusion, most people now use the term auto-commit instead.
- Explicit are user-defined transactions where you've explicitly defined the begin/commit.



Slide 26 – From the demo

This is from the lock escalation demo. This picture shows how the boundaries define the logical placement of data within the 3 partitions. All this pic is describing (briefly) is that the two RIGHT boundary points of 8000 and 16000 define the breakdown as follows:

$-\infty$ to 7999	8000 to 15999	16000 to ∞
Partition 1	Partition 2	Partition 3



Slide 36 (a bit deeper on relaxed fifo)

This was just a further discussion about the process that occurs when the update lock is converted to an exclusive lock. The discussion really focused back on the anatomy of a data modification. The conversion does not occur until SQL Server has to process the row. So, in a large/longer running transaction, you might have many update locks acquired and then as the data is processed, the rows are converted. Until the conversion is requested, shared locks are also allowed on these rows (even while the update lock is waiting) because of relaxed fifo. However, once the conversion is requested then ALL locks will wait.

BT


Upd saving

Upd check

BT

up check

up saving




Upd check
Upd saving

Upd check W
Upd saving

Slide 48 – Reducing deadlocks

Deadlocks often occur when resource patterns are interleaved. Where possible, rewriting code can be really helpful. A simple example is “the banking transaction” where one user is moving money from checking to savings and the other from savings to checking. This “crisscross” of activity will be more prone to deadlocking. One option (because this is a transaction) is to reorder the statements of the transactions to always access the tables in a particular order. If this were the case then these deadlocks would be removed and replaced with blocking (not deadlocks).



Deadlocks in an Index

This picture described a deadlock that can occur when multiple indexes exist on a single table and they INCLUDE columns that are being updated.

CL = clustered table

Left side = index on SSN INCLUDE (lastname)

Right side = index on firstname INCLUDE (lastname)

Imagine an update to firstname that uses WHERE SSN = running at the same time as an update to lastname that uses WHERE Lastname = (let's not debate how bad this latter update is ☺).

These updates are MUCH more likely to create deadlocks because of how locking works within indexes. To reduce the potential here – I often use sp_tableoption.

Set xact_abort OFF (default)

B T

update → succeed

Update →


← ~~Update~~ — fails lock timeout ^{user defined}

You have to decide

User-defined Errors in Transactions

If you hit a resource error, SQL Server will definitely rollback. However, if you hit a user-defined error condition (for example a constraint violation or a lock timeout), then the DEFAULT behavior is that YOU have to [programmatically] decide what to do. This requires GOOD error handling.

If you change the setting for XACT_ABORT (off by default) then ALL errors will cause a transaction to rollback.



For Developers

Savepoints (SAVE TRANSACTION) are a “stack” even when in the bounds of a stored procedure. The only “scope” for these is the “one” transaction in which they are a member.

For Developers (Transaction Madness)

The key points are:

BEGIN TRANSACTION

- Increments @@trancount

COMMIT TRANSACTION

- Decrements @@trancount


ROLLBACK TRANSACTION

- When used with a transaction name OR without a name at all – always resets @@trancount to 0 and cancels ALL pending transactions – no matter how deeply nested.

A transaction is NOT committed until @@trancount = 0. When transactions are nested you MUST COMMIT for every BEGIN

Savepoint (SAVE TRANSACTION NAME) do NOT affect @@trancount and can be rolled back to safely without affecting @@trancount.

A stored procedure is NOT a transaction in and of itself. You MUST use BEGIN/COMMIT to engage the ACID properties of the statements of a stored procedure.



Be sure to go through the demo scripts if you need more insight into transactions!

TRAN BT 1

Se _____

U _____

For Developers

Savepoints (SAVE TRANSACTION) are a “stack” even when in the bounds of a stored procedure. The only “scope” for these is the “one” transaction in which they are a member.

Save tran SP1

{

exec p1

BT 2

{

Save tran SP2

{

EXEC SP2

CT 1

stack

The rollback that's below actually rolls back to the LAST savepoint (SP1) in the stack. You'll want to make sure that every save point is unique and well-named.

}

IP

ROLLBACK TRAN SP1

}

CT 2

BT

Upd ~~~~~ success

Upd ~~~~~ suc

[Upd - statement rolled back

↳ violates cons.

↳ hit lock-timeout

trans. is still pending

}

if xact_abort
on

CT

Slide 56 (for developers)

If a statement of a transaction hits a USER-DEFINED error – what happens?

It's up to the application to determine the fate of the transaction.

In this case, if the 3rd statement errors with Error 1222 (Lock request time out period exceeded.) then the statement will be rolled back but the transaction will be pending.

This is the default behavior when SET XACT_ABORT is not on.

Having better error handling – writing code within TRY/CATCH blocks is essential for reducing errors and increasing data integrity.


SQLskills Immersion Event

IE1: Internals and Performance

Module 4: Snapshot Isolation

Kimberly L. Tripp
Kimberly@SQLskills.com





Demo: Non-repeatable reads (Inconsistent Analysis)


This is showing how an update to a CL key value that causes record relocation (after another query has already read [and released the lock on] the row) allows the reader to read the row TWICE (non-repeatedly).

This is from the demo on non-repeatable reads and shows what I called the “anderson-zembrowsky” problem. 😊

RC



Repeatable
reads




Demo: Why does RC (read committed) have non-repeatable reads?


Because the row-level shared locks are released immediately after the row is read.

Increasing your isolation level to repeatable reads gets rid of this problem by LEAVING the row-level shared locks for the life of the transaction. Guaranteeing that once a row has been read – it will not be able to be changed by another transaction/user.

Discussion: Phantoms (Inconsistent Analysis)

What is correct? Are we talking about row-consistency or statement-level consistency? The standards only define the state of the row at the time that the row is accessed. There is NOTHING that ties together the state of those rows at the time the query is accessed (unless you use versioning). So, here I was discussing the fact that NEW rows that are coming into the set will be visible in all isolation levels (except serializable). I always think of this scenario like a dog chasing its tail. 😊





Discussion: How does repeatable read prevent the Anderson/Zembrowsky problem?

As rows are read, the shared locks used to read them are left behind to protect the rows. The rows cannot be read again in any other state because the shared locks will prevent other users from modifying the rows.

X Sales

-


-

-

-

Country

Albama
 Argentina
 Australia
 Australia



Ar

A2

Alb
 A
 ✓
 Arge.
 S

Argo
 S
 Aus
 I

Aus

Aust
 S
 Austk
 }

Av

Key-range locking (Serializable transactions)

See the next two drawings/notes for more information on this.

Key range
locking
Serializable

leaf
real
data




NC
Country

Key-range locking (Serializable transactions)

This picture described key range locking in an index. When a query runs the isolation level dictates the state of the data (even in the bounds of a transaction) that we should see. In a serializable transaction the data is isolated at the time the statement runs. As a result, data must be locked at that time. To prevent new rows from coming into the set, SQL Server will lock the “range” of rows affected by the query. If a good index exists then SQL Server can lock within the index (it’s in the first intermediate level – the level above the leaf level). If a good index does not exist then SQL Server must do table-level locking.

Serializ-




S20 – Snapshot Isolation vs. Serializable transactions


Sometimes I like to say that S.I. is more serializable than the locking based serializable transaction isolation level is. The reason why – S.I. defines the point to which all statements reconcile as the BEGINNING of the transaction. All statements in the transaction reconcile to EXACTLY that same point in time (defined by an LSN). However, serializable can only lock resources AS it requests them. In this picture I drew that distinction – each statement locks AS it executes. So, the 2nd and 3rd statements reconcile to t2 (time 2) and t3 (time 3). Whereas a S.I. transaction would always reconcile to t1.

See slide 24 for more information on transaction-level read consistency = Snapshot Isolation (using versioning).


RC locking



RC NOLOCK



RC Versioning



The prior slide showed a table vertically as a set of pages. The idea was to compare/contrast the behaviors between:

(1) The default – READ COMMITTED (using locking)


The key things to remember from the picture is that (1) has “hiccups” along the way as they encounter rows that are locked. They read... wait... read... wait. This is *partially* what slows down a statement. However, it’s worse than this. It’s possible that AFTER a row is read, it will appear again (if the record is relocated) and we will read it twice (non-repeatable reads). Also, it’s possible that another transaction would modify a row that we’ve NOT yet seen (before we get there) as well as a row that we have seen (after we’ve read it) such that the end result of our statement has rows that aren’t really transactionally consistent (with another multi-statement transaction). This is also a problem... The default (1) environment is prone to a few inconsistencies (aka. Inconsistent analysis). Only way to solve – increase isolation (or [as of 2005] consider using versioning).

(2) A forced NOLOCK

The key thing to remember here is that no lock allows the reader to read quickly – not stopping for locked rows. However, these rows may be “in-flight” and their modified data might end up getting rolled back or even be in a mid-flight state. If you’re looking for only an estimate – this might be fine.


(3) Versioning (and it was implied that it was statement-level)

When a versioned query runs the reader will not stop but will have to go to the version store for any row that’s in flight. This is a tiny bit slower but guarantees consistency of the ENTIRE read to the point in time when the statement started. This gives you better concurrency as well as a definable point in time to which your statement reconciles. Of course, it isn’t free – the overhead of versioning is for every writer and it occurs within tempdb.



An ideal use for Snapshot Isolation


The idea is that you don't want to impact your production OLTP environment with READERS or with versioning so instead, you replicate to subscribers and use read committed snapshot there!



An ideal use for Snapshot Isolation

Taking that same idea a bit further – you could use WLBS (windows load balancing services) to create a server federation and let windows to load balancing by virtualizing the IP. But, to update these you'd have to have dual NICs and a bit more complicated setup.

SSD = Scalable Shared Databases



~~WUBS~~

For a SINGLE copy of a database on LUNs set to Read Only

You can create a federation using SSD (Scalable Shared Databases). Check out the BOL:

[http://technet.microsoft.com/en-us/library/ms345392\(v=sql.105\).aspx](http://technet.microsoft.com/en-us/library/ms345392(v=sql.105).aspx)

SQLskills Immersion Event

IE1: Internals and Performance

Module 6: Index Internals

Kimberly L. Tripp
Kimberly@SQLskills.com



CL must unique

LN

666

Smith
Smith 1

SSN

Jone
Jones 1

The Clustering key **MUST** be unique

The key reason that the clustering key must be unique is because of the lookup that must be performed when looking up a corresponding row from a nonclustered index request.


The uniquifiers are unique per duplicate key value

The FIRST Smith that is inserted is unique – so no uniquifier

The second Smith goes in and it becomes Smith 1


The FIRST Jones that is inserted is unique – so no uniquifier

The second Jones goes in and it becomes Jones 1



CL DATE

Int 2.147 bill




$\varepsilon_{r \text{ rov}}$

666

A clustering key should be unique by definition. However, if the CL key is NOT unique then SQL Server will uniquify it. And, this process of uniquification can be expensive because the next uniquifier value is unknown (they must scan the last page of values in that duplicate range).



Each duplicate group can support $2^{31}-1$ duplicates. What happens if you put a CL index on Lastname and then have 2 billion rows with a value of Smith? Error 666.

Error 666: The maximum system-generated unique value for a duplicate group was exceeded for index with partition ID %l64d. Dropping and re-creating the index may resolve this; otherwise, use another clustering key.



Another negative associated with the uniquifier value is finding it. Remember, each duplicate has a uniquifier that's tied only to it. On insert, SQL Server will have to scan the last page to find the maximum *current* value for the uniquifier for that "group." If you have something like a DATE (not datetime/datetime2) then you're likely to have an impact from the generation of the uniquifier. It's often better to use something like an invoice number to unify the rows. And, secondarily this should also save time. Because the uniquifier has to live in the variable block it requires at least 6 bytes and possibly 8. These additional bytes are in the data rows and in ALL indexes. If 90% of your data rows include the uniquifier AND many of your nonclustered indexes include the invoice number then you're going to be require less storage with an int and probably even still with a bigint given that the table won't need the uniquifier and many indexes [probably] already have the invoice number.


21




S12 – Forwarding pointers and back pointers (HEAPs ONLY)

This picture shows the overhead needed (in terms of bytes) for forwarding records. On the page where the record was inserted originally (to which ALL indexes will always point – as it's our “fixed RID”) will still have the header, the RID and the slot in the slot array (11 bytes). On the page where the row has been forwarded – you'll have a back pointer. This back pointer is 8 bytes but it lives in the variable block in the row so it requires an additional 2 bytes. Total space wasted is 21 bytes.

LOAD




Load



High Performance Loading Discussion

Some really good questions about "high performance loading" that lead to a discussion around these key things:


- **Loading into a HEAP** – typically this is best when you don't have an ordered file *and* when you can performance parallel load and parallel index creation.
- **Loading into a Clustered Table with an Ordered Load** – typically this is best when you have an ordered file and you cannot perform a parallel load and/or parallel index creation.
- **Loading into a Clustered Table with all nonclustered indexes pre-created** – this is almost NEVER a good idea unless you're loading only a small amount of data into an existing table. Typically less than 10% new data.




Clustering for range queries looks GREAT on paper... until modifications occur!

This was just reminding you that when folks tell you that the clustered index should be DESIGNED to support range queries you need to remind them of what the table is going to look like when there are modifications. What sounded good (the data is all together) doesn't stay that way...


- INSERTs/UPDATEs are slower due to the splits
- This wastes disk space AND memory because of the fragmentation caused.
- And the range query is no longer left-right ordered but instead very out of order (fragmentation)



SQL Server 7.0's storage engine was almost a complete rewrite. A major change in the engine around the method used from nonclustered indexes to lookup the corresponding row in the table (heap or clustered). In 7.0 and higher, SQL Server uses a FIXED RID (for heaps) and the clustering key (for tables with a clustered index). In 6.x, SQL Server used a volatile RID for ALL tables (regardless of whether they were clustered or not).



Even if your “primary” table uses a GUID for inserts... You might want to use an IDENTITY column as your foreign key. This takes less data space, less index space and results in a less expensive join. And, this might be an easier “conversion” to make for your application. You can potentially make it over time and through changes to some tables, some procs and then some code. Then, more tables, more procs and other code, etc. Slowly you can remove the old GUID columns and eventually become free of GUIDs as clustering keys and GUIDs for joins! You might still have a GUID on that initial table but only as a nonclustered PK. 😊



Take offline

DROP FKs

DROP NCs

DROP CL\PK

Add new column

CR CL

CR PK NC


CR NCs

CR FKs

Bring Online

What does it take to change a CL PK?

Unfortunately, A LOT. And, because of the lack of indexes and foreign keys – the entire process is OFFLINE. This is why this is such an important decision to make early!



Again, discussions about converting an existing application/database over time.

Phase I:

Add an identity column and cluster it (which includes (1) taking the database offline (2) dropping FKs, dropping NCs and finally, dropping the CL. (3) Add the identity column and cluster it. (4) Create the PK as NC. (5) Add back the other NCs. (6) Add back the FKs.

Phase II (you can do this for a subset of tables at a time, repeat until all are gone):

Migrate the related tables to use the Identity column for joins instead of the GUID-based FK. Slowly change code and eventually drop the GUID-based FK leaving ONLY the int-based FKs.



If you have only one file in a read-write filegroup you can potentially end up with contention on the system resources (PFS, GAM and SGAM). By having multiple files within the filegroup you can better handle contention.


Generally, I recommend 2-4 files in a read-write filegroup. You do NOT need 1 per core.

File / pfs / gam / sgam
Global Shared Global

NC Ind Gender



Non-unique nonclustered indexes MUST have the lookup key (the Heap's RID or the clustered table's clustering key) pushed up the tree. The reason stems from the fact that the rows would NOT be able to be found on a delete. And, it guarantees their position on an insert.



Fixing GUIDs


This scenario was from a question regarding the conversion of a database that uses GUIDs everywhere.

Completing eliminating GUIDs is tough to do. What you might do is something more gradual. Allow the application/user to continue to use the GUID as a nonclustered PK and then add a clustered identity. Slowly convert the related tables over by adding the identity column (as a FK back to the primary table) and then slowly remove this column altogether.

Table CL on EmpID

Key SSN
Inc LN

Key SSN
Leaf SSN, EmpID, LN



non-unique index on phone

Key phone
Inc LN

Key phone, EmpID
Leaf phone, EmpID, LN

S45

Where does the CL key go?

If the index is unique – then the CL is added only to the leaf-level.

If the nonclustered is non-unique – then the CL is added to leaf level as well as up the tree.


Specifically, it's added immediately after the key; included columns are added after that.

table's insert

index/ee inserts

1 NPT

CL index
inc key




PT w/ HASH

fs_0

CL Key
Hash/Col, ID
(if P)

fs_2

fs_3




Two types indexes on PT

Aligned


Unaligned

+ fast
switching

no fast
switching



whole
PT



We talked about this earlier in the week but this is a perfect context where unaligned indexes make sense.

Tangent on hash-based partitioning

SQLskills Immersion Event

IE1: Internals and Performance


Module 8: Internals and Data Access

Kimberly L. Tripp
Kimberly@SQLskills.com



4-5 10

2-3



1.6 million

~10K




2



~pk

ID

NC
Charge-no



~2100

Question/Discussion

This diagram was around the discussion of costing (of IOs) for lookups – between a heap and clustered table.

It **looks** like the CL index is worse:


Using a nonclustered to do a lookup (= 3 IOs), then – using the CL to lookup the data row = 3 more IOs for a total of 6 IOs

Whereas the heap seems to require fewer IOs. Using the nonclustered is about the same (=3 IOs), then – using the Heap to access the data row is 1 (possibly 2 if there's been record relocation) for a total of 4-5 IOs.

The long story short is that 4-5 IOs is less than 6 IOs. That *seems* better. Yes, the number is lower but the IOs are potentially more expensive. The yellow highlighting shows where the more expensive IOs are going to be performed (which is predominantly in the leaf structures).

As a result, a bookmark lookup from a NC to a clustered has 2 potentially physical IOs. The lookup from a NC to a heap has potentially 2-3 physical IOs.

While many lookups might be the same – there are still OTHER reasons for why heaps are not ideal. This is just yet-another-one. ☺



S16

Costing IOs for different indexes for the query on this slide.

The clustered is 1/8 of 4000 pages or 500 IO


The nonclustered index on SSN has to do a scan

But, a nonclustered covering index that was ordered EmpID then SSN (S17) would be a seekable nonclustered covering index with the fewest IOs as SQL Server would only have to read 1/8 of the 179 pages.

```
CREATE INDEX NCICovers4Cols
ON dbo.member
(lastname, firstname,
middleinitial, phone_no)
```

```
CREATE INDEX NCILNinKeyInc3Cols
ON dbo.member(lastname)
INCLUDE (firstname,
middleinitial, phone_no)
```

```
CREATE INDEX NCICovers4Cols
ON dbo.member
(lastname, firstname,
middleinitial, phone_no)
```




S29 – Keys and INCLUDE

In the first example all of the columns are in the key. The clustering key is added to the leaf-level and then all 5 columns go up the tree.

In the second example only lastname is in the key. The clustering key is added immediately after that (in the leaf-level) and then the included columns are added to the leaf-level. Then, only lastname and EmpID go up the tree. This is the best index for this query (if we were to tune query-by-query, which is completely unrealistic).

In the final example phone is the only include. The clustering key is added immediately after LN, FN, MI (in the leaf-level) and then phone is added. LN, FN, MI, EmpID go up the tree. This last example is the most realistic index but only after consolidation warrants it.




Solving an application problem with a filtered index

Somewhat recently I worked with an application that had a habit of adding % to the start/end of a queried value but only for a subset of data. However, that subset was not selective enough to use a nonclustered index. So, the query would do a complete table scan. This was causing huge performance problems... enter, filtered index!

We could cover the request but only where REGION = 'subset' so only that data would be scanned. OK, no, I didn't like the %value% search either but at least I could reduce the impact of it by using filtered indexes!

The negative – consistent session settings are required AND procedures must do a recompile to ensure that they will pick up the filtered index.



A foreign key can be used to reference any column (or list of columns) that has a unique index – as long as it's not filtered.

In an index consolidation scenario, if you already have a constraint on SSN and you NEED an index on SSN include (LastName) you'd end up with a "redundant" index (if SQL *required* a constraint-based index for foreign keys). Instead, you can drop the constraint on SSN and instead create:

```
CREATE UNIQUE NONCLUSTERED INDEX SSN_Inc_LN ON Member (SSN)
INCLUDE (LastName)
```

Foreign Keys can reference UNIQUE indexes (without constraints)

[http://www.sqlskills.com/BLOGS/KIMBERLY/post/Foreign-Keys-can-reference-UNIQUE-indexes-\(without-constraints\).aspx](http://www.sqlskills.com/BLOGS/KIMBERLY/post/Foreign-Keys-can-reference-UNIQUE-indexes-(without-constraints).aspx)


SQLskills Immersion Event

IE1: Internals and Performance

Module 9: Statistics


Kimberly L. Tripp
Kimberly@SQLskills.com





S11 – Column-level distribution from left-based density subsets...

This relates to the query on slide 10 and the idea that I was trying to show here is that even though the left-based density shows that last names are horribly NOT unique and the combination of last name & first name IS *almost* unique – that doesn't imply anything about first names alone. I could have created a data set of firstnames of Kima, Kimb, Kimc and then multiplied that with last names (Tripp, Randal, Smith) and I would have had similar statistics for last name alone and for the combination of last name, first name. SQL Server does NOT gamble on this – SQL Server creates column level statistics on first name.



S19

This is a diagram showing the pros/cons of the methods for statistics invalidation. SQL Server 7.0 and 2000 used a rowmodctr (sysindexes.rowmodctr) to do invalidation. Even though SQL Server doesn't use this anymore – you can (through the backward compatibility view sysindexes). In 2005+ they moved to an internally defined colmodctr:

- The pro is that you don't invalidate too soon (when you have a highly volatile column)
- The con is that you might not invalidate soon enough if your modifications are reasonably distributed.

in

X				X		X	
		X			X		X


row mod ctr 20%

|||||

S19


This shows how relatively distributed modifications effect each column with a small percentage of the modifications but when they add up to 20% ALL columns become invalidated (this was the PRE-2005 way of doing it):

- The pro was that each column had a reasonable (but lower) percentage of rows modified and the stats were invalidated
- The con is that a single overly volatile column would cause ALL statistics to be invalidated (which was overkill).



S19

The problem prior to 2005 was that a single overly volatile column would cause ALL statistics to be invalidated.




20%

S19

In 2005+ they use an internally defined colmodctr:

- The pro is that you don't invalidate too soon (when you have a highly volatile column)
- The con is that you might not invalidate soon enough if your modifications are reasonably distributed.




S28

Filtered statistics can be created for specific values but depending on your data distribution – you might want to divide the data into buckets and then create a [filtered] statistic for each of those buckets. The example was 31 million sales over ~18K customers. By creating a statistic for each 1K customers you have statistics that are effectively 19x more detailed. Even just 10 buckets gives you 10 times more detail. However, it still might not be detailed enough. You'll need to test it and check the histogram. Because of potential **interval subsumption*** issues– some have asked if it would be beneficial to create additional stats at different intervals... you could but it would really depend on the queries. Having said that – the bigger the range that the query is interested the more the averages are more accurate. So, really, this issue is to significantly help queries that are more targeted (where the stats just weren't good).

* The optimizer can detect whether interval conditions in a filtered index cover, or "subsume" interval conditions of a query.


1/20 of data 200K cost 10K



Creating Filtered Stats

The idea is to just have better statistics than what you have currently. To do this you can divide the range into 10-20 buckets. This will give you 10 times (or 20 times) better information in terms of statistics.


You WILL need to regularly/automatically review the values/ranges and add more or divide them up again to ensure that the statistics are good (and stay good)!



Simple vs. Forced Parameterization

The general process is that SQL Server analyzes a query to determine if it's safe or not (the majority of them will **NOT** be safe). If it's safe then it can get parameterized and reused. If it's unsafe then it goes into memory as an individual query (and it's harder to determine the cumulative effect of these queries). Check out the query_hash and query_plan_hash.

table



Status = 1

filter = 1

Query



Where Status = 1


Simple analyze use index

Forced status = @1

Filtered Stats and Forced Param

The bad news... there's always bad news.

Forced parameterization: even when SQL Server would NOT have parameterized the statement (because it had deemed the statement's plan as "unsafe" to re-use), forced param will force it. In systems where plans are very stable (but A LOT of adhoc) then this could be great. However, the example of status = 1 (in your query) is converted to status = @1 so the filtered index/filtered stat cannot be used.



Simple

Status = 1 not
save plan

Forced

Status = @1

Filtered indexes and filtered stats – Auto update

The bad news... there's always bad news.

For Updates:

statistics for a filtered index OR a filtered stat – do NOT get updated until that column's statistics get updated (which is when the colmodctr) is reached

F1
F1
F1
F1

~~Status = 1~~

Status = @1

Database option: FORCED parameterization

Because of how forced parameterization changes each variable to a parameter – the value of that parameter is unknown. As a result, a filtered index (for example, WHERE status = 1) cannot be used when a query has been parameterized to status = @1. There's no guarantee that the value they're searching on is 1.

End result. You will NOT have good results with filtered indexes IF you use FORCED parameterization. **The good news:** This is NOT on by default and not likely to be on in most environments.

TS ?

FactInternetSales2

DEMO

This was the demo on uneven distribution.

A table scan is always an option.

With narrow indexes, SQL Server does not understand the correlation between these columns. As a result, their estimates are going to assume even distribution.


NC

Index on ShippedDate



NC



Index on OrderDate



when will I hit
a NULL

$$\frac{2541}{60348} = \frac{1}{23.7}$$

Missing
Index
DMV



Sort

DEMO

This was the suggested index from the green hint in showplan and while it does make this query faster (and with fewer I/Os) it's not the best index that's possible.

Key point, the missing index DMVs (which is where the green hint gets its information from) – gives you good suggestions but not always the best suggestion.

Furthermore, this is the same index that's recommended by DTA. So... sometimes it does take *manually* defining/choosing the index.



DEMO

This was the index that I suggested (putting OrderDateKey in the key) as a combination of:

ShipDateKey, OrderDateKey

The first record on the first page will be the minimum OrderDateKey where ShipDateKey IS NULL.

Poor Man's DW

OLTP → B/R

Poor Man's Datawarehousing

Setting a database to RO (read-only) can be a good idea when you plan to use it solely for reads. However, how does SQL Server update statistics or add statistics?

Really, it can't.

So, the main point... if you're going to move a backup to another server for read-only access –you should automate some basic optimizations before setting it to RO.

① Update stats ←

② Rebuild Indexes

FF = 100

~~Update stats~~ ←

Sampling?

③ sp_createstats

Index only

Full scan - ?

READ ONLY

SQLskills Immersion Event

IE1: Internals and Performance

Module 10: Indexing Strategies

Kimberly L. Tripp
Kimberly@SQLskills.com



fn, ln

fn like K%

and LN = 'Sm'

Katie S

Katie U

Kiera R

Kiera T

K

Indexing for AND

If the columns are doing range-based searching then the order of the secondary columns of the index might not be relevant (or even required in the key).

This case was shown around the conditions:


WHERE firstname LIKE 'k%'

AND region_no > 6

AND member_no < 5000

Really, it doesn't matter what follows firstname because the entire set of firstnames will need to be scanned.

Loop Joins



filter
3
indexed
100 rows
10 pages

match
index
j.c
filter
100 rows
10 pages

Here we started to talk about how LOOP joins are an iterative process. The driver (the outer/first table) is typically chosen because it has the most selective set. Any of the tables that have a highly selective search argument are more likely to be chosen as the driver. An index that aids in efficiently finding those rows is REALLY helpful!

Cost can be calculated as:

Number of IOs required for first table +
Number of resulting rows in first table * the cost for each lookup (ideally with an index on the join condition)

- IF -

no good indexes
SQL HAD to
do loop

SCAN

$$10 + (100 \times 10)$$

In the worst case scenario the costing of this iterative process can be very high/expensive.

Instead of doing this, SQL Server is much more likely to do a loop join.

Loop Joins continued

If our query was:


```
SELECT columns (irrelevant here)
FROM Employee AS E
      JOIN Department AS D
            ON E.DID = D.DID
WHERE D.city = 'Redmond'
```

And, there were only 1 or 2 rows for Redmond in the Departments table then that's more likely to be positioned as the driver in the join.

Once we know the DIDs then we're going to need to find all of the employees IN that department. We'll need to search against the DID column in the Employee table.

Key question:


Do you have an index on the foreign key column?




where d.city = 'Redmond'

Merge

Cost



=



Sales

Merge Joins

Merge joins leverage "suitably sorted sets."

More specifically, merge leverages indexes whose leading keys are on the same column.

Key question:


What columns do these two tables have in common?

The join column...

Corollary question:

Do you have indexes on EACH of the columns (in each table)? The one that's often missing: the join column that's the foreign key.

HASH



Hash Joins

Hash are a little more complicated. There are multiple hash types available in SQL Server and each provide different benefits. The general purpose of a hash join is to significantly reduce the number of rows that have to be processed.

More specifically, there are two phases:

BUILD phase

PROBE phase

The build phase is used to create a small structure into which the larger set can probe to determine if there's the possibility of a matching row.


Two very good resources:

[Hash joins and hash teams in Microsoft SQL Server](#)

by Goetz Graefe, Ross Bunker, Shaun Shaun Cooper

[Query Evaluation Techniques for Large Databases](#)

by Goetz Graefe




Try to find your:

* Problem Child Table
(the table with the highest cost)

* Problem Child Join
(the join – typically downstream
from the table – with the highest
cost)

S17

Tuning a large complex join takes breaking it down into smaller chunks. The things that you consider are the costs of the tables (the outer most events) and the costs of the joins. And, typically, the most expensive join is downstream from the most expensive table.



S20

An index on a join column (the foreign key) helps the performance for the referential integrity as well as *some* joins. A narrow index on the join column helps but is often superseded by wider indexes; it's still a good start. (hence the phase – phase 1)


This is the most ideal for (but not limited to) a loop join.

Emp




where d.city = 'Redmond'

Dept.



Changing Join Order based on SARGs

An index on a join column (the foreign key) helps the performance for the referential integrity as well as some joins because your more selective criteria might be on the referencing table rather than the referenced.



A Foreign Key can reference

- Primary Key
- Unique Key
- Any unique index (even with INCLUDE but not with filters)

Blog Post:


<http://www.sqlskills.com/blogs/kimberly/foreign-keys-can-reference-unique-indexes-without-constraints/>

Two phase

stop

& go


build/probe



Hash Joins are “stop and go” operations (or two-phase operations)

Phase I – Build (this is the phase where they build a table to fit in cache)

Phase II – Probe (this is where the larger set uses the join condition to “probe” into the build/temp table to output matches). Probe cannot “go” until after build completes (hence the term – stop and go).




CRUCIAL IND (GRBY)
ON VIEW




Indexed Views

Are results sets defined by a view and materialized into the leaf level of the UNIQUE CLUSTERED INDEX that's defined on the view.




S50

The reason that `COUNT_BIG(*)` over the `GROUP BY` class is needed is because they need the count to determine when the row within the indexed view should be deleted. A zero sum is not enough.



Hot Row

If your aggregate is too small then you can have a HOT ROW problem where all modifications are blocked trying to write to the aggregate. You'll serialize your inserts by country here... CAN, MEX, USA are the only countries with whom you do business – all US rows will have to wait as each updates the sum. This will become a terrible bottleneck.



M10

If you create a partition aligned indexed view and then request something like the `sum(sales)` for customer #1 then SQL Server can aggregate the aggregates!

On SQL Server 2008, when you're switching in – you must defined the Views and IVs in order to successfully switch in.


SQLskills Immersion Event

IE1: Internals and Performance

Module 11: Partitioning

Kimberly L. Tripp
Kimberly@SQLskills.com





M11

- Partitioning in our module was all within a single database. However, we had a side/note about sharding and scale-out design. The most important thing that I can highlight is that scaling out is most ideal through middle-tier DDR (data-driven routing) where the applications are directed to the appropriate server. If every user randomly goes to any of these instances and all requests go through [distributed partitioned] views then performance will likely be worse!


Check out the whitepapers on SODA (service-oriented database architectures).



M11

Partitioning in our module was all within a single database. However, SQL Server does support Scalable Shared Databases. These are RO databases that are attached to multiple servers and then balanced through WLBS.

[Scalable Shared Databases](#)




M11

Be careful with partitioned views... there's nothing that's going to test your business logic. As a result, if you miss a day (for example Feb 29, 2008) then inserts into the view will fail because there's no view that can store that date.


Alternatively, using partitioned tables – there's no way to have a gap or overlapping ranges.

But, there's a lot more to PVs and PTs (this isn't enough to choose one over the other) so this is just a bit more info to add to the list!





M11

If a RW filegroup has a lot of allocations then you can have contention (much like that in tempdb). One of the best strategies is to make sure that all RW filegroups have at least 2 files and as many as four (as a default practice). You might need more but just moving from 1 is already going to eliminate many problems.




Application Directed Inserts (DSE)

Even with updateable partitioned views, I usually use application directed inserts. If you're concerned about dynamic string execution check out the Little Bobby Tables blog post: <http://www.sqlskills.com/BLOGS/KIMBERLY/post/Little-Bobby-Tables-SQL-Injection-and-EXECUTE-AS.aspx>




S17

Constraints are validated during optimization. SQL Server is able – when querying through a view – to generate the query tree and then “prune” the tree. This partition elimination removes any of the redundant tables from access. All of this is as long as the constraint is trusted (or, should I say as long as it’s NOT untrusted. 😊)



S17

Another way to look at this is that there are multiple phases of query processing. The second phase (standardization, normalization, algebraization) is where views are expanded to their base tables (known as EXPANDVIEWS). This might sound familiar because of the hint NOEXPAND – which is used to force SQL Server to use indexes on views (if for some reason SQL Server isn't using the IV).



Partitioning on integers (rather than date)


Another example of a partitioned table with 3 boundary points: 2million, 4 million and 6 million. It's a RIGHT-based partition function so the rows that match the boundary point will be to the RIGHT side. Specifically this translates into:

In partition 1: all rows less than 2 million

In partition 2: all rows equal to or greater than 2million and less than 4 million

In partition 3: all rows equal to or greater than 4million and less than 6 million

In partition 4: all rows equal to or greater than 6million




S30

Indexes can be aligned to the same partition scheme:

- Either by creating them ON SCHEME(col) or
- Accepting the default behavior during creation. Nonclustered indexes default to being created on the same scheme as the clustered index – unless they are an UNIQUE index. If the index is unique then the partitioning column must [explicitly] be part of the key.

Indexes can be unaligned

- The index has all of the nonclustered index data for the table in one leaf structure
- Fast-switching is NOT allowed if unaligned indexes exist



S37

For fast switching to be allowed – you must have ONLY aligned indexes. For an index to be aligned – there are rules. If the index is going to be unique (and aligned) then it MUST include the partitioning key. Indexes will default to being created on the same scheme as the table (they will default to being aligned – and therefore have all of these requirements).


However, if you're not interested in fast switching – then you can have un-aligned indexes. In this case you create these indexes on a specific filegroup (or on a different scheme). These un-aligned indexes can be unique and do NOT have to include the partitioning column.

S44

Why do you need a staging area?

- (1) So that you don't need to overallocate space within destination filegroups
- (2) So that you don't have to shrink (see s54)
- (3) So that you can optimize the process...


Always load into a staging area first.
Then, transform/cleanse
Then, build the CL index ON the destination filegroup!



~~E (E (June (July (Aug (Sep (Oct~~

If the MERGE process is slow
– you may have merged a
boundary point that was
NOT empty.


The most common case of this is when you start with a non-empty first partition using RIGHT-based partitioning. With RIGHT-based partitioning you should not MERGE until you have TWO empty partitions that surround the emptied boundary. Then, you can MERGE (top diagram).



S48


With PTs – it's likely that your last partition (often, the current data) will be active. This is also where it's most likely that you'll have fragmentation. If you want to rebuild ONLY that last partition – you'll need take it offline to do it.

OLTP



S48 (continued)

A better option is to separate the RW from the RO and put the RW in separate tables. Then, you can do online rebuilds at the table level. How do you deal with queries – put a partitioned view over them!



Criteria

Always 1 yr.
What if Q3 04

Scheme fs use next fgx
Function Split 20040701 boundary

merging

E

fs1

0701
2003
Q3

after switch

fs2

1001
2003
Q4

fs3

0101
2004
Q1

fs4

0401
2004
Q2

fgx

20040701
2004 Q3

Trust?

Constraint

OUT

CR 2003Q3 on fs1

CR CL

CR NC

CR V/IV

CR CS

drop table?

IN

Heap

load Staging
Cleanse (cl?)

ready for prod

CR CL on fgx

CR NC on fgx

CR V/IV

CR CS

2008+ →

2012+ →

The prior slide showed the sliding window scenario – but we went through it slowly:

(1) Preparing the table into which we'll switch OUT our old partition

Review all of the slides for the requirements here but the key point is that this “staging” table MUST be on the same filegroup as the partition you are going to switch out.

(2) Preparing the table for our data load and what will become our new partition to switch IN

Again, be sure to review all of the slides for the requirements here but one thing you need to make sure of is that there's a TRUSTED constraint on this table before you switch in.

(3) Change the partitioned table to support the new filegroup and data range

Always set the NEXT USED filegroup with ALTER SCHEME

Once you have the correct filegroup specified then ALTER FUNCTION...SPLIT

- Now, you're ready

(4) and (5) can be in any order. SWITCH IN the new partition and SWITCH OUT the old.


(6) Clean up


Merge the boundary point but ONLY if it's empty (the next picture will remind you of what happens when you don't MERGE an empty boundary point)

Backup the filegroup where the partition resides that you just switched out. OR, drop the table.

① merge

③ Scheme next used fsgp
split @ 20040701







With PVs - If you want to create indexed views, you must create them individually per table (for the tables that underpin the PV). If you're not on EE then you'll also need to create a specific view to access them with the (WITH NOEXPAND) hint.

S50


With PTs - If you want to create indexed views, you must create them as partition-aligned (for fast switching). This is a new feature of SQL Server 2008+






M11

You can have partitioned tables and/or non-partitioned tables that underpin a view. The only requirement – make sure that each of the tables (UNIONed in the view) has a constraint!x



M11

This was a drawing showing the possible compression of 3 columnstore-based indexes. Then, each columnstore index is broken down into segments. This is the base of batch-mode processing (another core part to the performance gains that can be recognized with columnstore indexes).



Might want to have CS indexes only on RO tables

SP
 (Q PT)
 (Q T)
 As
 select

Batch mode support


M11

Since columnstore indexes make the table on which they're created read-only then you might want to use PVs to separate read-write and read-only data.

Having said that, one limitation of the current implementation of nonclustered columnstore indexes is that they do not support batch mode processing across views that include UNION ALL. The workaround is to use CTEs.

Check out the discussion: **Perform UNION ALL and Still Get the Benefit of Batch Processing** on the columnstore wiki here:

<http://social.technet.microsoft.com/wiki/contents/articles/perform-union-all-and-still-get-the-benefit-of-batch-processing.aspx>



M11

There isn't a slide to which this applies. This was a side discussion about splitting a partition after it already has data.

If you forget to split for October and November and the last split was for Sept 1 – then, instead of splitting for October (which has to move BOTH October and November data) and then splitting for November (which has to move November's data again) – you should always split the last set (November) and then the earlier (October). Then, November's data only moves once and October's only once as well

However, if you're going to make significant changes to a partitioning scheme (like 4 partitions to 8) then instead of splitting 4 times – just create a new function and new scheme and then rebuild the object on the new scheme.


SQLskills Immersion Event

IE1: Internals and Performance

Discussion: Table Design Strategies

Kimberly L. Tripp
Kimberly@SQLskills.com





S4

This was a reminder that when you're calculating row size (as well as page density) that you can use 8096 for data rows. Every row requires 2 bytes in the slot array so two rows could each be 4046. However, a single row cannot be more than 8060. The 8060 comes from:

8192 bytes (page size)

- 96 bytes in the header

= 8096 as the maximum amount of space for data

A row must have a header of 4 bytes

= 8092 and the SQL team took "32 bytes" for future growth.

Some of which they're already using in SQL Server 2005 and higher. For row versioning, each versioned row requires a 14 byte offset. If they had allowed a row to be 8096 – where would they have put the offset?


				2	2
	VC	VC	VC	VC	VC
_____	X		X	X	2
_____				X	2
_____		X		X	2

Column order does not matter... it depends!

OK, this diagram should remind you that leaving the columns that are most likely to be null – at the end of the row definition *COULD* save some space.

Blog post: Column order doesn't matter... generally, but - IT DEPENDS!

<http://www.sqlskills.com/BLOGS/KIMBERLY/post/Column-order-doesnt-matter-generally-but-IT-DEPENDS!.aspx>



LOB

100-200
bytes MB

majority

< 2000 bytes

S7

Default behavior of a *new* LOB (max or XML) is that they will be put "in_row" if they fit (if the total row size is under 8060).

If you have a lot of small LOBs (for example 2K LOBs) then all of your rows will be really wide. If you're doing a lot of scans and NOT interested in always returning the LOBs then you're going to waste a lot of pages/IOs to get the LOBs into cache when you don't really need them.

Consider pushing these small LOBs off-page instead!

S8 Implicit Conversions

When a predicate is being evaluated there are two sides to the equation:

The column expression & The variable expression

When one of the expressions has a higher data type AND they're implicitly compatible then SQL Server will need to bring the other expression UP to the same type.


If the variable expression is the LOWER type then it's easy, only that variable has to be converted.

The problem starts when the column expression is the lower type – then the column has to be converted. This results in a scan of that column (could be an index scan but if a good index doesn't exist then it might be a table scan).

You can see implicit conversions in cache – check out Jonathan Kehayias' blog post on this:

Finding Implicit Column Conversions in the Plan Cache

http://sqlblog.com/blogs/jonathan_kehayias/archive/2010/01/08/finding-implicit-column-conversions-in-the-plan-cache.aspx




Placeholder Rows

Client $\longrightarrow$ ID def. def
VC VC VC VC

P/C
C
C
C
C





where LOB
 and check sum = checksum(LOB)

This was a tangent where we talked about a way to optimize lookups for LOB data.

One of the things that always causes people grief is that columns over 900 bytes cannot be indexed. So, if you have a WHERE clause like this:

```
WHERE lobcolumn = 'lob value.....'
```

SQL Server has to do a table scan to get all of this data.

Another trick is:

Add a CHECKSUM column that checksums a particularly large column (note: legacy LOB column types: (n)text, image AND XML are not supported – see this link: [http://msdn.microsoft.com/en-us/library/ms189788\(v=sql.105\).aspx](http://msdn.microsoft.com/en-us/library/ms189788(v=sql.105).aspx)) and then rewrite your queries to be this:

```
WHERE lobcolumn = 'lob value.....'
```

```
AND checksumcol = CHECKSUM('lob value.....')
```